
### **Spec Sheet**

# SMD Power Inductors (NR series S type) NRS4010T3R3MDGG



#### Features

- Item Summary
  - 3.3uH±20%, 1.1A, 4.0x4.0x1.0mm
- Lifecycle Stage
- Mass Production
- Standard packaging quantity (minimum)
  Taping Embossed 5000pcs


#### Products characteristics table

· · · · · · · · · · · · · · · · · · ·				
Inductance	3.3 uH $\pm$ 20 %			
Case Size (mm)	4.0x4.0			
Rated Current (max)	1.1 A			
Saturation Current (max)	1.1 A			
Saturation Current (typ)	1.3 A			
Temperature Rise Current (max)	1.4 A			
Temperature Rise Current (typ)	1.7 A			
DC Resistance (max)	0.12 Ω			
DC Resistance (typ)	0.1 Ω			
LQ Measuring Frequency	100 kHz			
Self Resonant Frequency (min)	58 MHz			
Operating Temp. Range	-25 to +125 ℃ (Including-self-generated heat)			
Temperature characteristic (Inductance change)	± 20 %			
RoHS2 Compliance (10 subst.)	Yes			
REACH Compliance (173 subst.)	Yes			
Halogen Free	Yes			
Soldering	Reflow			

#### External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.0 mm
Dimension e	1.1 ±0.2 mm
Dimension f	2.5 ±0.2 mm

#### Recommended Land Patterns



The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the Date at any time without notice. Before making final selection, please check product specification. 2017.04.30

**TAIYO YUDEN** 

unit : inch

(0.157 +/- 0.008)

## SMD Power Inductors (NR series S type)

Dimension

Length :


## NRS4010T3R3MDGG





Width :	4.0 +/- 0.2		(0.157 +/- 0.008)				
Height :	1.0	max.	( 0.039	max. )			
	0.0		( <b>.</b>				
Inductance :	3.3	ин	( test freq a	at 0.1MHz)			
DC Resistance :	0.1	/ 0.12	ohm ( ty	p/max)			
Saturation Current : 1,100 mA (max)							
Temp. rise Current : 1,400 mA (max)							
Saturation current typical: 30% reduction from initial L value.							
Temp rise Current typical : Temperature will rise by 40 deg C							

unit : mm

4.0 + / - 0.2







The data is reference only. Electrical characteristics vary depending on environment or measurement condition. TAIYO YUDEN reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.